

Spacer, Sleeve

5365-01-059-0666

NSN 5365-01-059-0666 · NIIN 010590666

FSC 5365 — Bushings, Rings, Shims, and Spacers · FSG 53 — Hardware and Abrasives

GOVERNMENT RECORD, CITED

ALSO SEARCHED AS 5365-01-059-0666 · 5365010590666 · NIIN 010590666 · 01-059-0666 · FSC 5365 Bushings, Rings, Shims, and Spacers

NEARBY STOCK NUMBERS ← 5365-01-059-0665 · 5365-01-059-0667 →

FEATURES

- Spacer,sleeve — FSC 5365
- Corner Shape: SQUARE ALL CORNERS
- Surface Treatment Document and Classification: QQ-P-416,TYPE 2,CLASS 2 FED SPEC SINGLE TREATMENT RESPONSE OVERALL
- Body Outside Diameter: 0.2400 INCHES MINIMUM AND 0.2600 INCHES MAXIMUM IN
- Style Designator: SOLID, PLAIN, NO OUTSIDE FLANGES
- Material Document and Classification: MIL-T-6732,TY 1,HT-125 MIL SPEC 1ST MATERIAL RESPONSE OR MIL-S-6050,COND F MIL SPEC 1ST MATERIAL RESPONSE OR MIL-T-6736,TY 1,HT-125 MIL SPEC 2ND MATERIAL RESPONSE OR MIL-S-6758,COND F MIL SPEC 2ND MATERIAL RESPONSE OVERALL
- Body Inside Diameter: 0.1270 INCHES MINIMUM AND 0.1330 INCHES MAXIMUM IN
- Specification/standard Data: 80205-NAS42 PROFESSIONAL/INDUSTRIAL ASSOCIATION STANDARD

IDENTIFICATION

- NSN: 5365-01-059-0666
- NIIN: 010590666
- FSC: 5365 — Bushings, Rings, Shims, and Spacers
- FSG: 53 — Hardware and Abrasives

GENERAL DESCRIPTION

The Spacer,sleeve, cataloged under National Stock Number 5365-01-059-0666, is classified within Federal Supply Class 5365 (Bushings, Rings, Shims, and Spacers) of the Hardware and Abrasives group. Government technical data includes 9 specifications, cited from the U.S. Government catalog. 1 additional reference document (drawings, advisory and superseded references) is recorded in the U.S. Government catalog. Current acquisition status: Active.

TECHNICAL SPECIFICATIONS

PARAMETER	VALUE
NSN	5365-01-059-0666
Item Name	Spacer,sleeve
FSC / FSG	5365 / 53 — Bushings, Rings, Shims, and Spacers
Status	ACTIVE
Corner Shape	SQUARE ALL CORNERS
Surface Treatment Document and Classification	QQ-P-416,TYPE 2,CLASS 2 FED SPEC SINGLE TREATMENT RESPONSE OVERALL
Body Outside Diameter	0.2400 INCHES MINIMUM AND 0.2600 INCHES MAXIMUM IN
Style Designator	SOLID, PLAIN, NO OUTSIDE FLANGES
Material Document and Classification	MIL-T-6732,TY 1,HT-125 MIL SPEC 1ST MATERIAL RESPONSE OR MIL-S-6050,COND F MIL SPEC 1ST MATERIAL RESPONSE OR MIL-T-6736,TY 1,HT-125 MIL SPEC 2ND MATERIAL RESPONSE OR MIL-S-6758,COND F MIL SPEC 2ND MATERIAL RESPONSE OVERALL
Body Inside Diameter	0.1270 INCHES MINIMUM AND 0.1330 INCHES MAXIMUM IN
Specification/standard Data	80205-NAS42 PROFESSIONAL/INDUSTRIAL ASSOCIATION STANDARD

PARAMETER	VALUE
Surface Treatment	CADMIUM AND CHROMATE OVERALL
Material	STEEL COMP 8630 OR STEEL COMP 4130 OVERALL

LIFECYCLE & COMPLIANCE

Acquisition Status	ACTIVE
DEMIL Code	DEMIL A – NO DEMILITARIZATION REQUIRED
Hazard	NO HAZARD CODE IN THE DLA RECORD (HMIC N)
Criticality Code	X

CROSS-REFERENCE INDEX

No manufacturer part numbers on file in the U.S. Government catalog.

REFERENCE DOCUMENTS

REFERENCE	MEANING
NAS42HT4-9	3/2 Design control – primary reference U.S. Government activity

No interchangeability data on file.

OTHER ITEMS IN FSC 5365 – BUSHINGS, RINGS, SHIMS, AND SPACERS

Items in the same Federal Supply class. No interchangeability or substitution relationship is implied.

5365-00-000-6078 5365-00-000-6078 · Item name not on file	5365-00-000-7436 5365-00-000-7436 · Item name not on file	5365-00-001-1292 PLUG,MACHINE THREAD	5365-00-001-1365 5365-00-001-1365 · Item name not on file
5365-00-001-1841 RING,TORQUE,TUBE,INBOARD,RUDDER	5365-00-001-1915 5365-00-001-1915 · Item name not on file	5365-00-001-1916 5365-00-001-1916 · Item name not on file	5365-00-001-1940 5365-00-001-1940 · Item name not on file

FREQUENTLY ASKED QUESTIONS

What is NSN 5365-01-059-0666?

NSN 5365-01-059-0666 is a Spacers,sleeve, classified under FSC 5365, Bushings, Rings, Shims, and Spacers. Status: active.

What are the specifications of 5365-01-059-0666?

Key specifications for 5365-01-059-0666: Corner Shape: SQUARE ALL CORNERS; Surface Treatment Document and Classification: QQ-P-416,TYPE 2,CLASS 2 FED SPEC SINGLE TREATMENT RESPONSE OVERALL; Body Outside Diameter: 0.2400 INCHES MINIMUM AND 0.2600 INCHES MAXIMUM IN; Style Designator: SOLID, PLAIN, NO OUTSIDE FLANGES. 9 specifications are documented in the U.S. Government catalog.

Is NSN 5365-01-059-0666 hazardous material?

No hazard code in the DLA record (HMIC N). Hazard information on this page is shown exactly as it appears in the DLA record.

SOURCES

U.S. Government catalog: edition PUBLOGDVD v12.0.0 (OCT 2026), edition date 2026-10-01, retrieved 2026-10-16.
U.S. Government catalog: edition PUBLOGDVD v12.0.0 (OCT 2026), edition date 2026-10-01, retrieved 2026-10-18.

PartsTable — the parts reference. Every fact cited to its source.
partstable.com/parts/5365-01-059-0666

✓ Data cited from the U.S. Government catalog; commercial cross-references from OEM and certified industry sources.
🇺🇸 PartsTable Design LLC · partstable.com